





This rivet type should be selected wherever a **vapor or liquid-tight fastener** is required! They provide **100% mandrel retention!** They also have 23% more tensile strength and up to 45% more shear strength than equivalent open-end types.



**Dome Head**



**120° Countersunk Head**

TYPE OF RIVET	DIA	MFG PART #	BYLER PART #	GRIP RANGE	DIMENSIONS			MIN STRENGTH LBS.		HOLE SIZE DRILL #
					L max	H	E	SHEAR	TENSILE	
<b>DOME HEAD</b> Aluminum Rivet/ Aluminum Mandrel	1/8	AD42AH	0611040214	.063-.125	.316	.236	.051	105	150	.129-.133 #30
		AD43AH	0611040314	.126-.187	.377					
		AD44AH	0611040414	.188-.250	.440					
<b>DOME HEAD</b> Aluminum Rivet/ Aluminum Mandrel	5/32	AD54AH	0611050414	.063-.125	.455	.312	.066	155	240	.160-.164 #20
		AD62AH	0611060214	.063-.125	.345					
		AD64AH	0611060414	.126-.250	.470					
<b>DOME HEAD</b> Aluminum Rivet/ Aluminum Mandrel	3/16	AD66AH	0611060614	.251-.375	.595	.375	.081	220	310	.192-.196 #11
		AD68AH	0611060814	.376-.500	.720					
		AD62AH	0611060214	.063-.125	.345					
<b>DOME HEAD</b> Aluminum Rivet/ Steel Mandrel	1/8	AD41H	0612040114	.032-.062	.255	.236 .260	.051	305	385	.129-.133 #30
		AD42H	0612040214	.063-.125	.316					
		AD43H	0612040314	.126-.187	.377					
		AD44H	0612040414	.188-.250	.440					
		AD45H	0612040514	.251-.312	.502					
		AD46H	0612040614	.313*.375	.565					
	5/32	AD52H	0612050214	.063-.125	.330	.312	.066	430	605	.160-.164 #20
		AD53H	0612050314	.126-.187	.392					
		AD54H	0612050514	.188-.312	.517					
	3/16	AD62H	0612060214	.063-.125	.345	.375	.081	575	84	.192-.196 #11
		AD64H	0612060414	.126-.250	.470					
		AD66H	0612060614	.251-.375	.595					
1/4	AD84H	0612080414	.126-.250	.505	.500	.099	900	1100	.257-.261 F"	
	AD86H	0612080614	.251-.375	.630						
	AD64SSH	0613060414	.126-.250	.470						
<b>DOME HEAD</b> Aluminum Rivet/ Stainless Steel Mandrel	3/16	AD66SSH	0613060614	.250-.375	.595	.375	.081	575	840	.192-.196 #11
		AK41H	0612040124	.031-.062	.297					
<b>120° COUNTERSUNK HEAD</b> Aluminum Rivet/ Steel Mandrel	1/8	AK42H	0612040224	.063-.125	.361	.233	.050	305	385	.129-.133 #30
		AK43H	0612040324	.126-.187	.422					
		AK44H	0612040424	.188-.250	.486					
		AK45H	0612040524	.251-.312	.548					
		AK53H	0612050324	.126-.250	.452					
	3/16	AK64H	0612060424	.126-.250	.540	.375	.075	575	840	.192-.196 #11
AK66H		0612060624	.251-.375	.665						
<b>DOME HEAD</b> Stainless Steel Rivet/ Stainless Steel Mandrel	1/8	SSD41SSH	0633040114	.000-.063	.258	.262	.039	472	499	.129-.133 #30
		SSD42SSH	0633040214	.063-.125	.313					
		SSD43SSH	0633040314	.125-.188	.379					
		SSD44SSH	0633040414	.188-.250	.441					
		SSD45SSH	0633040514	.250-.309	.504					
	5/32	SSD52SSH	0633050214	.000-.125	.338	.338	.042	742	899	.160-.164 #20
		SSD53SSH	0633050314	.125-.188	.394					
		SSD54SSH	0633050414	.188-.250	.461					
	3/16	SSD55SSH	0633050514	.250-.309	.523	.393	.049	966	990	.192-.196 #11
		SSD62SSH	0633060214	.032-.125	.359					
		SSD64SSH	0633060414	.126-.250	.488					
	1/4	SSD66SSH	0633060614	.250-.371	.605	.525	.099	1528	1955	.257-.261 F
SSD68SSH		0633060814	.371-.496	.723						
SSD84SSH		0633080414	0.00-.250	.555						
SSD86SSH	0633080614	.371-.496	.801							

\*\*\*Minimums may apply\*\*\*

+ Values shown are a guide only and may vary depending on the application